

AIR DRILL SPECIFICATIONS

5000HD



3-SECTION MODEL, ft. (m)		27' (8.2)	28' (8.5)	33' (10.1)	34' (10.4)	39' (11.9)	40' (12.2)
DIMENSIONS							
Transport, ft. (m)	Length	29' (8.8)	29' (8.8)	29' (8.8)	29' (8.8)	29' (8.8)	29' (8.8)
ft. in. (m)	Height	11' 6" (3.5)	11' 6" (3.5)	14' 6" (4.4)	14' 6" (4.4)	17' 6" (5.3)	17' 6" (5.3)
ft. in. (m)	Width	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)
NUMBER OF SHANKS							
Spacing, in. (cm)	7.2" (18.3)	45	—	55	—	65	—
in. (cm)	10" (25.4)	—	34	40	—	—	48
in. (cm)	12" (30.5)	—	28	—	34	—	40
5-SECTION MODEL, ft. (m)		45' (13.7)	46' (14.0)	51' (15.5)	52' (15.8)	57' (17.4)	58' (17.7)
DIMENSIONS							
Transport, ft. (m)	Length	29' (8.8)	29' (8.8)	29' (8.8)	29' (8.8)	29' (8.8)	29' (8.8)
ft. in. (m)	Height	13' 6" (4.1)	13' 6" (4.1)	17' 6" (5.3)	17' 6" (5.3)	16' 11" (5.2)	16' 11" (5.2)
ft. in. (m)	Width	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)	20' 6" (6.2)
NUMBER OF SHANKS							
Spacing, in. (cm)	7.2" (18.3)	75	—	85	—	95	—
in. (cm)	10" (25.4)	—	56	62	—	—	70
in. (cm)	12" (30.5)	—	46	—	52	—	58
TIRES							
5000HD CONFIGURATION, ft. (m)		27, 28, 33 and 34' (8.2, 8.5, 10.1 and 10.4)		39, 40, 45 and 46' (11.9, 12.2, 13.7 and 14.0)		51, 52, 57 and 58' (15.5, 15.8, 17.4 and 17.7)	
		Single caster tires on front (11L-15FI D-Rating - 6-bolt hubs)		Dual caster tires on front (9.5L-15FI D-Rating - 6-bolt hubs)		Dual caster tires on front (11L-15FI D-Rating - 6-bolt hubs)	
		Tires on rear walking beams (9.5L-15FI D-Rating - 6-bolt hubs)		Tires on rear walking beams (9.5L-15FI D-Rating - 6-bolt hubs)		Tires on rear walking beams (11L-15FI D-Rating - 6-bolt hubs)	
		Tires on wing sections (9.5L-15SL 6-ply - 6-bolt hubs)		Tires on wing sections (9.5L-15SL 6-ply - 6-bolt hubs)		Tires on wing sections (9.5L-15SL 6-ply - 6-bolt hubs)	
SPACING							
4-row, in. (cm)		7.2, 10 or 12" (18.3, 25.4 or 30.5) spacings					
FRAME/GROUND CLEARANCE, in. (cm)							
		28 to 32" (71.1 to 81.3) depending on openers and depth settings					
CULTIVATOR-STYLE TRIPS							
		350 lb. (160 kg) with 1 x 2 in. (2.5 x 5.1 cm) shank, 1 3/4 in. (4.4) centers fit 47° sweeps					
		350 lb. (160 kg) with 1 x 2 in. (2.5 x 5.1 cm) shank, 2 1/4 in. (5.7) centers fit 50° sweeps					
		550 lb. (250 kg) with 1 x 2 in. (2.5 x 5.1 cm) shank, 1 7/8 in. (4.8) centers fit 47° sweeps					
		550 lb. (250 kg) with 1 x 2 in. (2.5 x 5.1 cm) shank, 2 1/4 in. (5.7) centers fit 50° sweeps					
PRESS WHEELS							
Rubber, in. (cm)		3 x 22" (7.6 x 55.9) 4 x 22" (10.2 x 55.9) 5 1/2 x 22" (14 x 55.9)					
Steel, in. (cm)		3 1/2 x 22" (8.9 x 55.9) 4 1/2 x 22" (11.4 x 55.9)					
OPTIONS							
		Shim kits to lower shanks behind tractor wheels		Tow hitch for NH ₃ cart		Dual offset caster for the center section of	
		Single or dual end markers		Bolt-on caps for steel press wheels		27, 28, 33 and 34 ft (8.2, 8.5, 10.1 and 10.4 m) models	
		Press wheel mud scrapers		1-bar heavy harrow for 4-row configuration		Dual offset caster for the wing sections (all models)	
						NH ₃ control interface for Raven AccuFlow	

ASAE 279.11 TRANSPORT LIGHTING IS STANDARD EQUIPMENT

Every effort has been made to produce these specifications with the most current information available. However, ongoing product development and improvements mean that the equipment and specifications are subject to change without notice. © 2005 CNH America LLC

For up-to-date specifications, product feature details, or to locate your Flexi-Coil dealer, go to

WWW.FLEXICOIL.COM

It's your direct source for product information and much more.

