

PT SPRAYER SPECIFICATIONS

68/68XL



| MODEL | 68 | 68XL |
|-------------------------------------|--|--|
| Tank Sizes, U.S. gallons (L) | 1000 (3785) | 1600 (6056) |
| BOOMS | | |
| Suspended, ft. (m) | 80 (24.4) 48 nozzles at 20" (50.8 cm) spacing [optional 30" (76.2 cm)] 90 (27.4) 54 nozzles at 20" (50.8 cm) spacing [optional 30" (76.2 cm)] 100 (30.5) 60 nozzles at 20" (50.8 cm) spacing [optional 30" (76.2 cm)] | 120 (36.6) 72 nozzles at 20" (50.8 cm) spacing [optional 30" (76.2 cm)], no windscreen 134 (40.8) 80 nozzles at 20" (50.8 cm) spacing [optional 22" (56 cm)], no windscreen |
| Wheeled, ft. (m) | | |
| 4 section | | 80 (24.4) 48 nozzles at 20" (50.8 cm) spacing 84 (25.6) 50 nozzles at 20" (50.8 cm) spacing 90 (27.4) 54 nozzles at 20" (50.8 cm) spacing 94 (28.7) 56 nozzles at 20" (50.8 cm) spacing 100 (30.5) 60 nozzles at 20" (50.8 cm) spacing 104 (31.7) 62 nozzles at 20" (50.8 cm) spacing |
| 6 section | | 110 (33.5) 66 nozzles at 20" (50.8 cm) spacing 114 (34.8) 68 nozzles at 20" (50.8 cm) spacing 120 (36.6) 72 nozzles at 20" (50.8 cm) spacing 124 (37.8) 74 nozzles at 20" (50.8 cm) spacing 130 (39.6) 78 nozzles at 20" (50.8 cm) spacing 134 (40.8) 80 nozzles at 20" (50.8 cm) spacing |
| CART TIRES/TRACKING WIDTHS | | |
| Single | 18.4-26R3 (80"-120" tracking width) (203-305 cm) 380/80R38 (62"-120" tracking width) (157-305 cm) 320/90R46 (60"-120" tracking width) (152-305 cm) | 480/80R38 R1 (72"-120" tracking width) (183-305 cm) 380/90R46 R1 (72"-120" tracking width) (183-305 cm) 380/85R46 R1 (72"-120" tracking width) (183-305 cm) |
| Duals | 320/90R46 [22" (56 cm) rows, 132" (335 cm) outer spacing max.] 380/90R46 [30" (76 cm) rows, 120" (305 cm) outer spacing max.] | |
| TRANSPORT WIDTH | | |
| Suspended, ft. (m) | 11' (3.35) without windscreens 11'2" (3.4) with windscreens | |
| Wheeled, ft. (m) | 11'2" (3.4) wheeled boom fold arm width | |
| CLEARANCE | | |
| Cart Axle, in. (cm) | 33-36 (84-91) depending on tire options | |
| SUSPENDED BOOM HEIGHT RANGE | | |
| in. (cm) | 18-70 (46-178) | |
| PUMPS | | |
| Hydraulic Centrifugal, U.S. gpm (L) | Hypro™ HM1C for hydraulic oil flows of 8-15 (30-57) | |
| U.S. gpm (L) | Hypro HM3C for hydraulic oil flows of 15-23 (57-87) | |
| U.S. gpm (L) | Ace™ 206 for hydraulic oil flows of 6-9 (23-34) | |
| PLUMBING | | |
| Boom Control Valves | TeeJet™ 450 Series ball valve manifold system (flanged fittings) 1" (2.5 cm) hose boom control valves to booms 3.2 (12) | |
| Hand/Eye Wash Tank U.S. gallons (L) | 120 (460) Integrated in frame | |
| Fresh Water Tank U.S. gallons (L) | Four horizontal jet-type | |
| Agitation | 1" (2.5 cm) Schedule 80 PVC pipe (wheeled boom) | |
| Spray Booms | 1" (2.5 cm) Schedule Polypropylene (suspended boom) 1" (2.5 cm) Schedule 40 Stainless Steel (wheeled and suspended – optional) | |
| NOZZLES | | |
| | TeeJet™ visaflo flat fan, standard or extended range, 80 or 110 (degree) tips TeeJet™ single- or triple-head nozzle bodies Swivel-Jet double-head nozzle bodies Combo-Jet™ single-, double- or triple-head nozzle bodies and tips | |

PT SPRAYER SPECIFICATIONS

68/68XL



MODEL
ELECTRONICS
FlexControl® III
FlexControl® Plus III

68

7-in. colorscreen, soft button navigation, on-the-go rate changes, animated graphics, and configurable display
10-in. color screen, touch screen navigation, on-the-go rate changes, animated graphics, and configurable display

68XL

OPTIONS

Induction tank 12 U.S. gal (46 L) with c-seal and screw lid
Chemical container rinse standard on induction tank
Low-pressure wash wand
Windscreens
Endscreens (standard suspended)
Foam marker
Fender (for single tires)
Extra ball valve kit
End nozzles
Hydraulic fold out (wheeled boom)

Every effort has been made to produce these specifications with the most current information available. However, ongoing product development and improvements mean that the equipment and specifications are subject to change without notice. © 2008 CNH America LLC

For up-to-date specifications, product feature details, or to locate your Flexi-Coil dealer, go to

WWW.FLEXICOIL.COM

It's your direct source for product information and much more.

